

INDUSTRIAL COMPONENT DATA

PLC-V8L/FLK14/OUT 2299660 PHOENIX CONTACT System connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-V8L/FLK14/OUT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-V8L/FLK14/OUT
Catalog number	2299660
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-D8D85F7F5F
Generated	2026-08-01

Product Overview

System connection

V8 adapter for 8 x PLC-INTERFACE (14 mm), control: PLC wiring system for output cards, connection 1: 1x screw connection, connection 2: IDC/FLK 1x 14-pole male connector, connection 3: Plug-in connection (Fits into 8x PLC-INTERFACE terminals), number of channels: 8, control logic: plusschaltend

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2299660

Packing unit 1 pc

Catalog page Page 425 (C-5-2017)

GTIN 4017918893163

Weight per Piece (excluding packing) 77.900 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 112.5 mm

Height 39 mm

Depth 56 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

General

Max. perm. operating voltage 30 V DC

Max. perm. current (per branch) 1 A (per signal path)

Max. permissible current (separate power supply) 3 A

Number of positions 14

Status display Green LED

Mounting position any

Assembly instructions In rows with zero spacing

Degree of protection IP20

Connection data for connection 1

Connection name Supply

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Number of connections 1

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 14

Pitch 2.54 mm

Connection data for connection 3

Connection name Field level

Connection method Plug connection

Note Can be snapped onto 8x PLC-INTERFACE terminals

Supported controller

Controller SIEMENS S7-1500

- suitable I/O card 6ES7 522-1BH00-0AB0

6ES7 522-1BH01-0AB0

6ES7 522-1BL00-0AB0

6ES7 522-1BL01-0AB0

Controller SIEMENS S7-400

- suitable I/O card 6ES7 422-1BL00-0A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-V8L/FLK14/OUT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.