

INDUSTRIAL COMPONENT DATA

VAL-MS 230/3+1 FM/32 2908476 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 230/3+1 FM/32



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 230/3+1 FM/32
Catalog number	2908476
Category	Surge protection device for power supply systems
Minimum order	32 Pcs
Document ID	EO-2706567769
Generated	2026-08-06

Product Overview

Type 2 surge arrester

Surge arrester consisting of a base element with FM remote indication contact and plug-in protections, for installation on NS 35/7.5, nominal voltage: 230 V AC, circuit "3 + 1"

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Trabtech (TT)**

Additional Product Information

Key Commercial Data

Orderkey 2908476

Packing unit 32 pc

Minimum order quantity 32 pc

Note Made to Order (non-returnable)

GTIN 4055626305295

Weight per Piece (excluding packing) 402.500 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 98.7 mm

Width 71 mm

Depth 65.7 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 4 Div.

Ambient conditions

Degree of protection IP20 (only when all terminal points are used)

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

Mode of protection L-N

L-PE

N-PE

Mounting type DIN rail: 35 mm

Color jet black RAL 9005

Housing material PA 6.6

PBT

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 4

Surge protection fault message Optical, remote indicator contact

Protective circuit

Nominal voltage UN 240/415 V AC (TN-S)

240/415 V AC (TT)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous operating voltage UC(L-N) 275 V AC

Maximum continuous operating voltage UC(L-PE) 275 V AC

Maximum continuous voltage UC(N-PE) 260 V AC

Rated load current IL 80 A

Residual current IPE ≤ 5 µA

Standby power consumption PC ≤ 360 mVA

Nominal discharge current I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 230/3+1 FM/32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.