

INDUSTRIAL COMPONENT DATA

VAL-SEC-T2-3C-440-FM 2909968 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-SEC-T2-3C-440-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-SEC-T2-3C-440-FM
Catalog number	2909968
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-F6174CD65E
Generated	2026-08-05

Product Overview

Type 2 surge arrester

Plug-in surge arrester according to type 2/class II, for three-phase power supply networks with PE and N routing combined in one conductor (4-conductor system: L1, L2, L3, PEN), with remote indication contact.

Plug-in surge arrester, in accordance with Type 2/Class II, for 3-phase power supply networks with combined PE and N installed in one conductor (4-conductor system: L1, L2, L3, PEN), with remote indication contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Technical dataNotesGeneral

Note Usable in all low-voltage systems between L-N or L-PEN.

Only usable in IT Systems between L-PE, if the exposed-conductive-parts (bodies) of the equipment of the low-voltage installation is connected to the earthing arrangement of the transformer substation. (interconnected earthing arrangement of the HV-transformer substation with the bodies of the LV-installation. RE= RA accordance to IEC 60364-4-442 / VDE 0100-442 Fig. 44D / Example a)

Product propertiesProduct type Surge arrester

Product family SEC Family

IEC test classification II

T2

EN type T2

IEC power supply system TN-C
Type DIN rail module, two-section, divisible
Number of positions 3
Surge protection fault message Optical, remote indicator contact
Data management status
Article revision 03
Insulation characteristics
Overvoltage category III
Pollution degree 2
Electrical propertiesNominal frequency fN 50 Hz (60 Hz)
Indicator/remote signaling
Connection name Remote fault indicator contact
Switching function Changeover contact
Operating voltage 5 V AC ... 250 V AC
125 V DC (200 mA DC)
Operating current 5 mA AC ... 1 A AC
1 A DC (30 V DC)
Connection dataConnection method Screw connection
Screw thread M5
Tightening torque 4.5 Nm
Stripping length 16 mm
Conductor cross section flexible 2.5 mm² ... 16 mm²
Conductor cross section rigid 2.5 mm² ... 25 mm²
Conductor cross section AWG 12 ... 4
Connection method Fork-type cable lug
Conductor cross section flexible 1.5 mm² ... 6 mm²
Remote fault ind...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-SEC-T2-3C-440-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.