

INDUSTRIAL COMPONENT DATA

PC 5/ 8-G-7,62 BK 1708291 PHOENIX CONTACT PCB headers, number of positions: 8, pitch: 7.62 mm, color: black

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 8-G-7,62 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/ 8-G-7,62 BK
Catalog number	1708291
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-B36B49F26B
Generated	2026-08-03

Product Overview

PCB headers, number of positions: 8, pitch: 7.62 mm, color: black

Printed circuit board base housing, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 8, family of articles: PC 5/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1708291

Packing unit 1

GTIN 4046356995429

Custom tariff number 85366930

Dimensions

Length [L] 29.25 mm

Width 63.76 mm

Pitch 7.62 mm

Dimension a 53.34 mm

Width [w] 63.76 mm

Height [h] 19.29 mm

Height 14.29 mm

Length of the solder pin 5 mm

Length 29.25 mm

General

Range of articles PC 5/-G

Rated voltage (III/3) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 41 A

Color black

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 13.239121409

ETIM for 1708291 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

7.62 mm

Modular spacing connections (EF006827)

7.62 mm

Rated current In (EF008250)

41 A

Rated voltage (EF000228)

630 V

Rated surge voltage (EF002993)

6 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 8-G-7,62 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.