

INDUSTRIAL COMPONENT DATA

VAL-US-600D/30-P 2910341 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-US-600D/30-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-US-600D/30-P
Catalog number	2910341
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-35BA55F2E7
Generated	2026-08-03

Product Overview

Type 2 surge protection plug

Type 1 surge protection device, UL recognized component, and IEC Type 2 plug-in surge protection with varistor and thermal disconnect device for use with VAL-US base elements, mechanical and optical fault signaling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2910341

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626444833

Weight per Piece (excluding packing) 60.000 g

Custom tariff number 85363030

Country of origin US (United States)

Dimensions

Height 52.4 mm

Width 17.5 mm

Depth 55.3 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / $3x \pm X, \pm Y, \pm Z$)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

Mode of protection L-L

L-PEN

Mounting type on base element

Color jet black RAL 9005

Housing material PA 6.6

PBT

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type Male

Number of positions 1

Surge protection fault message optical

Protective circuit

Nominal voltage UN 554/960 V AC (TN)

Nominal frequency f_N 50 Hz (60 Hz)

Maximum continuous voltage UC 750 V AC

Residual current IPE $\leq 500 \mu A$ Standby power consumption PC ≤ 400 mVANominal discharge current $I_n(8/20) \mu s$ 15 kAMaximum discharge current $I_{max}(8/20) \mu s$ 30 kA

Short-circuit current rating ISCCR 25 kA

Voltage protection level $U_p \leq 2.9$ kVResidual voltage $U_{res} \leq 2.9$ kV (at I_n) ≤ 2.7 kV (at 10 kA) ≤ 2.5 kV (at 5 kA) ≤ 2.3 kV (at 3 kA)

TOV behavior at UT 1000 V AC (5 s / withstand mode)

1056 V AC (120 min / sa...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-US-600D/30-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.