

INDUSTRIAL COMPONENT DATA

SACC-V-4CON-PG9/A 1527883 PHOENIX CONTACT Valve connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-4CON-PG9/A



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-4CON-PG9/A
Catalog number	1527883
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-5FB46E2E49
Generated	2026-08-03

Product Overview

Valve connectors

Valve Connector, Universal, 4-Pole, Valve Connector A, Screw Connection, Pg9 Cable Gland, Cable Outer Diameter 6 mm ... 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > QUICKON Installation System (QPD)**

Additional Product Information

Key Commercial Data

Orderkey 1527883

Packing unit 1 pc

Catalog page Page 110 (PC-2009)

GTIN 4017918980955

Weight per Piece (excluding packing) 25.300 g

Custom tariff number 85366990

Country of origin HU (Hungary)

Dimensions

External diameter 6 mm ... 8 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 100 °C (connector)

Degree of protection IP65

General

Rated current at 40°C 10 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Connection method Screw connection

Conductor cross section $0.34 \text{ mm}^2 \dots 1.5 \text{ mm}^2$

Conductor cross section AWG 22 ... 16

Insertion/withdrawal cycles 50 (Valve connector)

Material

Flammability rating according to UL 94 HB

Valve plug contact material CuSn

Valve plug contact surface material Ni

Valve plug contact insert material PA6

Material housing valve plug PA6

Sealing material NBR (Flat gasket)

TPE (Screw connection)

Standards and Regulations

Connection in acc. with standard UL

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss

7.027440104eCl@ss 8.027440104eCl@ss 9.027440105

ETIM 2.0EC001121ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-V-4CON-PG9/A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.