

INDUSTRIAL COMPONENT DATA

FLKM 14-PA-MODI/M340 2903208 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 14-PA-MODI/M340



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 14-PA-MODI/M340
Catalog number	2903208
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-BFF61DA32E
Generated	2026-08-04

Product Overview

Front adapters

VARIOFACE Front Adapter for Schneider Electric Modicon M340

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Front adapter

Product family VARIOFACE

Data management status

Article revision 06

Insulation characteristics: Air clearances and creepage distances

Insulation Functional insulation

Overvoltage category II

Pollution degree 2

Electrical propertiesOperating voltage (AC) <= 30 V AC

Operating voltage (DC) <= 60 V DC

Nominal operating mode 100% operating factor

Current (per branch) <= 1 A

Current (Voltage supply via IDC/FLK) <= 3 A

Current (Voltage supply via Push-in connection) <= 10 A

Air clearances and creepage distances

Rated insulation voltage 63 V

Rated surge voltage 0.6 kV (1.2/50 us)

Supported controller SCHNEIDER ELECTRIC Modicon M340

Suitable I/O card BMX DDI 1602

BMX DDI 1603

BMX DAI 1602

BMX DAI 1603

BMX DDO 1602

BMX DDO 1612

Connection data Connection 1 (control level)

Connection method Plug-in connection

Number of connections 2

Number of positions 10

Pitch 7.5 mm

Connection 2 (field level)

Connection in acc. with standard IEC 60603-13

Connection method IDC/FLK pin strip

Number of connections 2

Number of positions 14

Insertion/withdrawal cycles > 50

Pitch 2.54 mm

Connection 3 (supply)

Connection method Push-in spring connection

Stripping length 10 mm

Number of connections 1

Number of positions 4

Conductor cross section rigid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

0.25 mm² ... 2.5 mm² (Ferrule without plastic sleeve)

0.25 mm² ... 1 mm² (Ferrule with plastic sleeve)

Conductor cross section flexible...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 14-PA-MODI/M340 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.