

INDUSTRIAL COMPONENT DATA

FLKM 50-PA-S400 2294500 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 50-PA-S400



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 50-PA-S400
Catalog number	2294500
Category	Accessories/spare parts for controls
Minimum order	2 Pcs
Document ID	EO-853650F499
Generated	2026-08-01

Product Overview

Front adapters

VARIOFACE front adapter, for Siemens SIMATIC® S7-400, 1x 32 channel connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Front adapter

Product family VARIOFACE

Data management status

Article revision 11

Insulation characteristics: Air clearances and creepage distances

Insulation Functional insulation

Overvoltage category II

Pollution degree 2

Electrical propertiesOperating voltage (AC) <= 30 V AC

Operating voltage (DC) <= 60 V DC

Nominal operating mode 100% operating factor

Current (per branch) <= 1 A

Current (Voltage supply via IDC/FLK) <= 2 A

Current (Voltage supply via spade connection) <= 8 A

Air clearances and creepage distances
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (1.2/50 us)
Supported controller SIEMENS S7-400
Suitable I/O card 6ES7421-1BL01-0AA0
6ES7422-1BL00-0AA0
6ES7422-7BL00-0AB0
Supported controller SIEMENS S7-400
Note Only in conjunction with
VIP-2/SC/FLK50/S7/A-S400, Item No. 2322359
VIP-2/PT/FLK50/S7/A-S400, Item No. 2904289
all DR wire bridges on the adapter must be disconnected.
Suitable I/O card 6ES7421-7BH01-0AB0
6ES7421-7DH00-0AA0
Connection dataConnection 1 (control level)
Connection method Plug-in connection
Number of positions 48
Connection 2 (field level)
Connection in acc. with standard IEC 60603-13
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 50
Insertion/withdrawal cycles > 50
Pitch 2.54 mm
Connection 3 (supply)
Connection method Spade connection
Number of positions 5
Note 2,8 x 0,8
DimensionsItem dimensions
Width 24.2 mm
Height 273.5 mm
Depth 67.6 mm
Environmental and real...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 50-PA-S400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.