


INDUSTRIAL COMPONENT DATA

FLKM 50/32M/PLC 2289719 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 50/32M/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 50/32M/PLC
Catalog number	2289719
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-297961445B
Generated	2026-07-31

Product Overview

Passive module

VARIOFACE interconnect module, for 32 channels with an additional terminal block per signal, for a common negative potential

VARIOFACE interface module, for 32 channels, each with an additional terminal block per signal for a common minus potential

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2289719

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 529 (C-5-2017)

GTIN 4017918057763

Weight per Piece (excluding packing) 315.080 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 192 mm

Height 90 mm

Depth 68 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 60 V DC

Max. perm. current (per branch) 1 A

Max. permissible current (separate power supply) 8 A (per byte)

Number of positions 50

Status display No

Mounting position any

Degree of protection IP00

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Number of connections 1

Number of positions 50

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 50

Pitch 2.54 mm

Supported controller

Controller SIEMENS S7-400

- suitable I/O card 6ES7 421-1BL01-0AA0

6ES7 422-1BL00-0AA0

6ES7 422-7BL00-0AB0

Controller ALLEN-BRADLEY ControlLogix

- suitable I/O card 1756-IB32

1756-OB32

Controller ALLEN-BRADLEY PLC 5

- suitable I/O card 1771 IBN

1771 OBN

Controller HONEYWELL Experion PKS C200

- suitable I/O card TC-IDD 321

TC-ODD 321

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 50/32M/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.