


INDUSTRIAL COMPONENT DATA

UMK-32 MDSTB/MKKDS3/R 2970196 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-32 MDSTB/MKKDS3/R



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-32 MDSTB/MKKDS3/R
Catalog number	2970196
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-46D0EA985A
Generated	2026-08-04

Product Overview

Interface module

VARIOFACE module, with screw connection and COMBICON plug-in connector, coded, for mounting on NS 35/7.5 or NS 32, number of poles 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2970196

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 599 (C-7-2015)

GTIN 4017918087685

Weight per Piece (excluding packing) 2.800 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 112.5 mm

Height 77 mm

Depth 58.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 250 V AC/DC

Max. perm. current (per branch) 3 A

Number of positions 32

Mounting position any

Connection data for connection 1

Connection name PCB connection

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 7 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 2.5 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 14

Number of connections 1

Number of positions 32

Connection data for connection 2

Connection name PCB connection

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Number of connections 1

Number of positions 32

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Down..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-32 MDSTB/MKKDS3/R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.