

INDUSTRIAL COMPONENT DATA

UMK- PVB 6 2972136 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-PVB 6



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-PVB 6
Catalog number	2972136
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-7FED2347DB
Generated	2026-08-02

Product Overview

Potential distributors

VARIOFACE module, with six equipotential connecting rods (P1, P2, P3, P4, P5, P6) for potential distribution, for mounting on NS 35/7.5 or NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2972136

Packing unit 1 pc

Catalog page Page 599 (C-5-2017)

GTIN 4017918088613

Weight per Piece (excluding packing) 398.200 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 123.8 mm

Height 77 mm

Depth 72 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Nominal voltage UN 250 V AC/DC

Max. current carrying capacity per branch 16 A

Total current 16 A (per potential)

Potential connections Per potential (P1...P6) 2 power/12 distributor terminal blocks

Mounting position any

Standards/regulations IEC 60664

DIN EN 50178

Rated surge voltage 2.2 kV (Functional insulation)

Rated insulation voltage 250 V

Degree of pollution 2

Overvoltage category II

Degree of protection IP20

Connection data, supply

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 6 mm²

Conductor cross section flexible 0.2 mm² ... 4 mm²

Conductor cross section AWG 24 ... 10

Number of connections 6

Connection data, distribution

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Rated insulation voltage 250 V

Rated surge voltage 2.2 kV (Functional insulation)

Degree of pollution 2

Overvo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-PVB 6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.