

INDUSTRIAL COMPONENT DATA

VIP-2/SC/D 9SUB/M 2315117 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D 9SUB/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/D 9SUB/M
Catalog number	2315117
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-0C53272AFD
Generated	2026-07-27

Product Overview

Interface module

VARIOFACE module, with screw connection and D-SUB miniature male connector, for mounting on NS 35 symmetrical rails, number of poles: 9

VARIOFACE module, with screw connection and male D-Subminiature pin strip, for mounting on NS 35 rails, 9-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE Professional

Number of positions 9

Data management status

Article revision 12

Insulation characteristics

Overvoltage category II

Pollution degree 2

Electrical propertiesNominal voltage UN 25 V AC

60 V DC

Max. current carrying capacity per branch 2 A

Rated surge voltage 1.2 kV

Connection dataField level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M 3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Tightening torque 0.5 Nm ... 0.6 Nm
Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 9
SignalingStatus display present No
DimensionsItem dimensions
Width 34.7 mm
Height 65.5 mm
Depth 45.1 mm
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V0
Housing insulation material Polyamide PA non-reinforced
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Standards and regulationsStandards/regulations IEC 60664
DIN EN 50178
MountingMounting type DIN rail mounting
Mounting position any
NotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed.
For applications or use with third-party products, the....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/D 9SUB/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.