

**INDUSTRIAL COMPONENT DATA**

# VIP-2/SC/D 9SUB/M/LED 2322142 PHOENIX CONTACT

## Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D 9SUB/M/LED



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | VIP-2/SC/D 9SUB/M/LED |
| Catalog number  | 2322142               |
| Category        | Interface module      |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-728F66B805         |
| Generated       | 2026-08-01            |

### Product Overview

Interface module

VARIOFACE module, with screw connection and miniature D-SUB male connector, for mounting on NS 35 symmetrical rails, with LED, number of poles: 9

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

### Additional Product Information

Key Commercial Data

Orderkey 2322142

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 571 (C-5-2017)

GTIN 4046356451765

Weight per Piece (excluding packing) 92.100 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 34.7 mm

Height 65.5 mm

Depth 45.1 mm

**Ambient conditions**

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

**General**

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 2.5 A

Number of positions 9

Status display LED

Mounting position any

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 9

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations IEC 60664

DIN EN 50178

Degree of pollution 2

Overvoltage category II

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

**Classifications**

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / VIP-2/SC/D 9SUB/M/LED with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.