

INDUSTRIAL COMPONENT DATA

VIP-2/SC/D15SUB/F 2315175 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D15SUB/F



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/D15SUB/F
Catalog number	2315175
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-7789859952
Generated	2026-08-01

Product Overview

Interface module

VARIOFACE module, with screw connection and D-SUB 15 plug-in connection, for installation on symmetrical NS 35 rails
VARIOFACE module, with screw connection and D-SUB 15 socket connector, for mounting on NS 35 rails

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE Professional

Number of positions 15

Data management status

Article revision 11

Insulation characteristics

Overvoltage category II

Pollution degree 2

Electrical propertiesNominal voltage UN 25 V AC

60 V DC

Max. current carrying capacity per branch 2 A

Rated surge voltage 1.2 kV

Connection dataField level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M 3

Conductor cross section rigid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Tightening torque 0.5 Nm ... 0.6 Nm

Controller level

Connection method D-SUB socket strip

Number of connections 1

Number of positions 15

SignalingStatus display present No

DimensionsItem dimensions

Width 45 mm

Height 65.5 mm

Depth 45.1 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0

Housing insulation material Polyamide PA non-reinforced

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Standards and regulationsStandards/regulations IEC 60664

DIN EN 50178

MountingMounting type DIN rail mounting

Mounting position any

NotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed.

For applications or use with third-party products, t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/D15SUB/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.