

INDUSTRIAL COMPONENT DATA

VIP-2/SC/D15SUB/F/LED 2322207 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D15SUB/F/LED



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/D15SUB/F/LED
Catalog number	2322207
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-9A048F67A2
Generated	2026-08-04

Product Overview

Interface module

VARIOFACE module, with screw connection and D-SUB miniature female connector, for mounting on NS 35 symmetrical rails, with LED, number of poles: 15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2322207

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 571 (C-5-2017)

GTIN 4046356451826

Weight per Piece (excluding packing) 117.000 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 50 mm

Height 65.5 mm

Depth 45.1 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 2.5 A

Number of positions 15

Status display LED

Mounting position any

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method D-SUB socket strip

Number of connections 1

Number of positions 15

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations IEC 60664

DIN EN 50178

Degree of pollution 2

Overvoltage category II

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/D15SUB/F/LED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.