

**INDUSTRIAL COMPONENT DATA**

# VIP-2/SC/HD15SUB/M 2322326 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/HD15SUB/M



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | PHOENIX CONTACT    |
| MPN / Reference | VIP-2/SC/HD15SUB/M |
| Catalog number  | 2322326            |
| Category        | Interface module   |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-43AB848B18      |
| Generated       | 2026-07-29         |

## Product Overview

Interface module

VARIOFACE module, with screw connection and high-density D-SUB miniature plug, for mounting on NS 35 symmetrical rails, number of poles: 15, width: 57 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

## Additional Product Information

Key Commercial Data

Orderkey 2322326

Packing unit 1 pc

Catalog page Page 591 (C-7-2015)

GTIN 4046356451253

Weight per Piece (excluding packing) 100.300 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 44.9 mm

Height 65.5 mm

Depth 45.1 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 25 V AC

60 V DC

Max. perm. current (per branch) 1 A

Number of positions 15

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Number of positions 15

Connection data for connection 2

Connection name Controller level

Connection method High density D-SUB pin strip

Number of connections 1

Number of positions 15

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations EN 50178

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss

7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 4.0E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/HD15SUB/M with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.