

**INDUSTRIAL COMPONENT DATA**

# VIP-2/SC/PDM-2/24 2315269 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/PDM-2/24



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | PHOENIX CONTACT                      |
| MPN / Reference | VIP-2/SC/PDM-2/24                    |
| Catalog number  | 2315269                              |
| Category        | Distributor assembly terminal blocks |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-39677B019E                        |
| Generated       | 2026-08-03                           |

## Product Overview

Potential distributors

VARIOFACE module with two busbars (P1, P2) for potential distribution, for installation on symmetrical NS 35 rails. Module width: 70.4 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Key Commercial Data

Orderkey 2315269

Packing unit 1 pc

Catalog page Page 268 (C-4-2017)

GTIN 4046356313377

Weight per Piece (excluding packing) 149.100 g

Custom tariff number 85369010

Country of origin US (United States)

Dimensions

Width 70.4 mm

Height 65.5 mm

Depth 50 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Nominal voltage UN 250 V AC/DC

Max. current carrying capacity per branch 15 A

Total current 30 A (per potential)

Potential connections Per potential (P1, P2) 2 power/12 distributor terminal blocks

Mounting position any

Standards/regulations IEC 60664

DIN EN 50178

Rated surge voltage 2.2 kV

Degree of pollution 2

Overvoltage category III

Connection data, supply

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 6 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section AWG 24 ... 10

Number of connections 2

Connection data, distribution

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Number of connections 24

Standards and Regulations

Connection in acc. with standard CSA

Standards/regulations IEC 60664

DIN EN 50178

Rated surge voltage 2.2 kV

Degree of pollution 2

Overvoltage category III

Environmental Product Compliance

China RoHS Envi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/PDM-2/24 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.