


INDUSTRIAL COMPONENT DATA

VIP-3/SC/D37SUB/M/LED 2322171 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/SC/D37SUB/M/LED



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/SC/D37SUB/M/LED
Catalog number	2322171
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-86A675A403
Generated	2026-07-29

Product Overview

Interface module

VARIOFACE module, with screw and blade connection D-SUB for mounting on DIN NS 35 rails, with LED, number of poles: 37.

VARIOFACE module, with screw connections and D-SUB pin strip, for mounting on NS 35 rails, with LED, 37-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE Professional

Number of positions 37

Data management status

Article revision 06

Insulation characteristics

Overvoltage category II

Pollution degree 2

Electrical propertiesNominal voltage UN 24 V DC

Max. current carrying capacity per branch 2.5 A

Connection dataField level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section rigid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Tightening torque 0.5 Nm ... 0.6 Nm

Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 37

SignalingStatus display LED

Status display present Yes

DimensionsItem dimensions

Width 72.7 mm

Height 69 mm

Depth 62 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0

Housing insulation material Polyamide PA non-reinforced

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Standards and regulationsStandards/regulations IEC 60664

DIN EN 50178

MountingMounting type DIN rail mounting

Mounting position any

NotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed.

For applications or use with third-party products, the specifications,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/SC/D37SUB/M/LED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.