

## INDUSTRIAL COMPONENT DATA

## VIP-3/SC/HD44SUB/F 2322427 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/SC/HD44SUB/F



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | PHOENIX CONTACT    |
| MPN / Reference | VIP-3/SC/HD44SUB/F |
| Catalog number  | 2322427            |
| Category        | Interface module   |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-9E5E6E1638      |
| Generated       | 2026-08-01         |

## Product Overview

Interface module

VARIOFACE module, with screw connection and high-density D-SUB miniature female connector, for mounting on symmetrical NS 35 rails, number of poles: 44, width: 135 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Key Commercial Data

Orderkey 2322427

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 576 (C-5-2017)

GTIN 4046356451727

Weight per Piece (excluding packing) 213.900 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 82.9 mm

Height 69 mm

Depth 62 mm

**Ambient conditions**

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

**General**

Max. perm. operating voltage 25 V AC

60 V DC

Max. perm. current (per branch) 1 A

Number of positions 44

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Number of positions 26

Connection data for connection 2

Connection name Controller level

Connection method High-density D-SUB socket strip

Number of connections 1

Number of positions 44

**Standards and Regulations**

Connection in acc. with standard CUL

Standards/regulations EN 50178

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

**Classifications**

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@s...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / VIP-3/SC/HD44SUB/F with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.