

INDUSTRIAL COMPONENT DATA

VIP-2/PT/FLK14 2903788 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/FLK14



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/FLK14
Catalog number	2903788
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-4DF67E2B86
Generated	2026-08-05

Product Overview

Interface module

VARIOFACE module, with push-in connections and plug-in connector for flat cable, for mounting on symmetrical NS 35 rails, with male connector as well as locking by short and long ties for connecting females, number of poles: 14

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2903788

Packing unit 1 pc

Catalog page Page 568 (C-5-2017)

GTIN 4046356796620

Weight per Piece (excluding packing) 100.000 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 41.9 mm

Height 72.1 mm

Depth 56 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 60 V AC/DC

Max. perm. current (per branch) 1 A

Number of positions 14

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 26 ... 14

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 14

Pitch 2.54 mm

Standards and Regulations

Connection in acc. with standard CSA

Standards/regulations IEC 60664

DIN EN 50178

Rated surge voltage 0.6 kV

Degree of pollution 2

Overvoltage category II

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss 7.02714...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/FLK14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.