

INDUSTRIAL COMPONENT DATA

VIP-3/PT/D37SUB/M/HW/C300 2904276 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/D37SUB/M/HW/C300



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/D37SUB/M/HW/C300
Catalog number	2904276
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-8064AF6805
Generated	2026-08-06

Product Overview

Interface module

VARIOFACE module, with push-in connections and D-SUB miniature male connector, for mounting on symmetrical NS 35 rails, number of poles: 37

VARIOFACE module, with push-in connections and male D-SUB miniature pin strip, for mounting on NS 35 rails, 37-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE Professional

Number of positions 37

No. of channels 16

Data management status

Article revision 05

Insulation characteristics

Overvoltage category II

Pollution degree 2

Electrical propertiesNominal voltage UN 25 V AC

60 V DC

Max. current carrying capacity per branch 2 A

Rated surge voltage 1.2 kV
Supported controller HONEYWELL Experion PKS C300/C-Series
Suitable I/O card TAOX01 (non-redundant)
TAOX11 (redundant)
TUIO31 (non-redundant)
TUIO41 (redundant)
Connection dataField level
Connection in acc. with standard IEC / EN
Connection method Push-in connection
Stripping length 8 mm
Number of positions 37
Conductor cross section rigid 0.14 mm² ... 4 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
SignalingStatus display no
Status display present No
DimensionsItem dimensions
Width 87.6 mm
Height 75.8 mm
Depth 63 mm
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V0
Housing insulation material Polyamide PA non-reinforced
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Standards and regulationsStandards/regulations EN 50178
MountingMounting type DIN rail mounting
Mounting position any
NotesNotes on operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/D37SUB/M/HW/C300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.