

INDUSTRIAL COMPONENT DATA

VIP-2/PT/D 9SUB/M 2903777 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/D 9SUB/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/D 9SUB/M
Catalog number	2903777
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-FBBFE92A48
Generated	2026-08-06

Product Overview

Interface module

VARIOFACE module, with push-in connections and D-SUB miniature male connector, for mounting on NS 35 symmetrical rails, number of poles: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2903777

Packing unit 1 pc

Catalog page Page 572 (C-5-2017)

GTIN 4046356796521

Weight per Piece (excluding packing) 89.600 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 36.8 mm

Height 72.1 mm

Depth 46.6 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 25 V AC

60 V DC

Max. perm. current (per branch) 2 A

Number of positions 9

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 26 ... 14

Connection data for connection 2

Connection name Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 9

Standards and Regulations

Connection in acc. with standard CSA

Standards/regulations IEC 60664

DIN EN 50178

Rated surge voltage 1.2 kV

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127371000eCl@ss 6.027371000eCl@ss
7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 4.0EC002...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/D 9SUB/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.