

INDUSTRIAL COMPONENT DATA

VIP-3/PT/PDM-2/16 2903797 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/PDM-2/16



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/PDM-2/16
Catalog number	2903797
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-57BB1438F3
Generated	2026-08-05

Product Overview

Potential distributors

VARIOFACE module with two busbars (P1, P2) for potential distribution, for installation on symmetrical NS 35 rails. Module width: 41.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2903797

Packing unit 1 pc

Catalog page Page 598 (C-5-2017)

GTIN 4046356796712

Weight per Piece (excluding packing) 121.200 g

Custom tariff number 85369010

Country of origin US (United States)

Dimensions

Width 41.9 mm

Height 75.8 mm

Depth 63 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Nominal voltage UN 250 V AC/DC

Max. current carrying capacity per branch 15 A

Total current 30 A (per potential)

Potential connections Per potential (P1, P2) 2 power/8 distributor terminal blocks

Mounting position any

Standards/regulations IEC 60664

DIN EN 50178

Degree of pollution 2

Overvoltage category III

Connection data, supply

Connection method Push-in-/Spring-cage connection

Stripping length 15 mm

Conductor cross section solid 0.25 mm² ... 6 mm²

Conductor cross section flexible 0.25 mm² ... 4 mm²

Conductor cross section AWG 24 ... 10

Number of connections 2

Connection data, distribution

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 26 ... 14

Number of connections 16

Standards and Regulations

Connection in acc. with standard CSA

Standards/regulations IEC 60664

DIN EN 50178

Degree of pollution 2

Overvoltage category III

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/PDM-2/16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.