

INDUSTRIAL COMPONENT DATA

UMK-16 RELS/KSR-G24/21/E/PLC 2974891 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-16 RELS/KSR-G24/21/E/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-16 RELS/KSR-G24/21/E/PLC
Catalog number	2974891
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-5D376416FD
Generated	2026-08-02

Product Overview

Active module

VARIOFACE output expansion module, with plug-in sockets for 16 miniature relays, with 1 switched contact each, for 24 V DC (without relays)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2974891

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 539 (C-5-2017)

GTIN 4017918088996

Weight per Piece (excluding packing) 4.400 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 259 mm

Height 77 mm
Depth 59 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Input data
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN 2 mA (Light indicator)
Type of protection Free-wheeling diode
Protective circuit/component Damping diode
Operating voltage display Green LED
Status display/channel Yellow LED
Output data
Contact type 1 PDT
Maximum switching voltage 250 V AC/DC
Limiting continuous current 4 A
Status display Yes
Error detection (line break / short-circuit) no
General
No. of channels 16
Compatible components Miniature relay, REL-MR- 24DC/21HC
With components no
Mechanical service life 3x 10⁷ cycles
Operating mode 100% operating factor
Degree of protection IP00
Mounting position any
Assembly instructions In rows with zero spacing
Color green
Connection data for connection 1
Connection name Coil side
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 20
Pitch 2.54 mm
Connection data for connection 2
Connection name Contact side
Conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-16 RELS/KSR-G24/21/E/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.