


INDUSTRIAL COMPONENT DATA

UMK- 8 RELS/KSR-G24/21/PLC 2974914 PHOENIX CONTACT

Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-8 RELS/KSR-G24/21/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-8 RELS/KSR-G24/21/PLC
Catalog number	2974914
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-A20DB43E5F
Generated	2026-08-03

Product Overview

Active module

VARIOFACE output module, with plug-in sockets for 8 miniature relays, with 1 switched contact each, for 24 V DC (without relays)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2974914

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 538 (C-5-2017)

GTIN 4017918089016

Weight per Piece (excluding packing) 228.000 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 135 mm

Height 77 mm

Depth 59 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC

Type of protection Free-wheeling diode

Protective circuit/component Damping diode

Type of protection Reverse polarity protection

Protective circuit/component Polarity protection diode

Operating voltage display Green LED

Status display/channel Yellow LED

Output data

Contact type 1 PDT

Maximum switching voltage 250 V AC/DC

Limiting continuous current 5 A

Error detection (line break / short-circuit) no

General

No. of channels 8

Compatible components Miniature relay, REL-MR- 24DC/21HC

With components no

Mechanical service life 3x 10⁷cycles

Operating mode 100% operating factor

Degree of protection IP00

Mounting position any

Assembly instructions In rows with zero spacing

Color green

Connection data for connection 1

Connection name Coil side

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 14

Pitch 2.54 mm

Connection data for connection 2

Connection name Contact side

Connection method Scre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-8 RELS/KSR-G24/21/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.