

INDUSTRIAL COMPONENT DATA

UM 25-D 9SUB/B/FRONT/Q 2959560 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 25-D 9SUB/B/FRONT/Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM 25-D 9SUB/B/FRONT/Q
Catalog number	2959560
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-6F5AD6818F
Generated	2026-08-05

Product Overview

Interface module

VARIOFACE SLIM-LINE, with screw connection and subminiature female connector D, for transverse mounting on NS 35/7.5, number of poles 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2959560

Packing unit 1 pc

Catalog page Page 574 (C-5-2017)

GTIN 4017918086213

Weight per Piece (excluding packing) 79.950 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 25 mm

Height 117 mm

Depth 45 mm

Ambient conditions

Ambient temperature (operation) -10 °C ... 50 °C

Ambient temperature (storage/transport) -10 °C ... 70 °C

General

Max. perm. operating voltage 25 V AC

60 V DC

Max. perm. current (per branch) 2.5 A

1.5 A (with even load on all branches)

Number of positions 9

Mounting position any

Degree of protection IP20

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method D-SUB socket strip

Number of connections 1

Number of positions 9

Standards and Regulations

Standards/regulations DIN EN 50178

IEC 60664

Rated insulation voltage 125 V

Rated surge voltage 1.2 kV (Functional insulation)

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.02...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 25-D 9SUB/B/FRONT/Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.