

INDUSTRIAL COMPONENT DATA

VDFK 6/K GNYE 0711069 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: VDFK 6/K GNYE



Manufacturer	PHOENIX CONTACT
MPN / Reference	VDFK 6/K GNYE
Catalog number	0711069
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D4A294BF4E
Generated	2026-08-05

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Welded connection, number of poles: 1, charging current: 41 A, cross-section: 0.2 mm² - 10 mm², conductor connection direction with respect to the plug direction: 0 °, width: 10 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 0711069

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 293 (CL-2002)

GTIN 4017918105518

Weight per Piece (excluding packing) 7.800 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current I_N 57 A
Nominal voltage U_N 500 V
Open side panel No
Number of positions 1
Dimensions
Width 10 mm
Pitch 10 mm
Plate thickness 1 mm ... 4 mm
Connection data
Connection side outside
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 8
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 6 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 4 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VDFK 6/K GNYE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.