


INDUSTRIAL COMPONENT DATA

VIOK 1,5-3D/PE-EX 3024465 PHOENIX CONTACT

Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIOK 1,5-3D/PE-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIOK 1,5-3D/PE-EX
Catalog number	3024465
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-ABF8D30223
Generated	2026-08-05

Product Overview

Sensor/actuator terminal block

Terminal block for detectors/actuators, nominal voltage: 400 V, nominal current: 24 A, connection type: Screw connection, 2nd, 3rd, and 4th floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3024465

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918282790

Weight per Piece (excluding packing) 27.530 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 4

Number of connections 7

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)

Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2

Nominal current IN 24 A

Maximum load current 26 A (with a 2.5 mm² conductor cross section)

Nominal voltage UN 400 V (when using EB insertion bridges, the nominal voltage is reduced to 250 V.)

Open side panel No

Dimensions

Width 6.2 mm

Length 82.5 mm

Height NS 35/7,5 70 mm

Height NS 35/15 77.5 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross sect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIOK 1,5-3D/PE-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.