

INDUSTRIAL COMPONENT DATA

VIP-2/PT/D37SUB/M/ET200SP-HA 1100964 PHOENIX CONTACT VARIOFACE module for the SIMATIC ET200SP HA with push-i..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/D37SUB/M/ET200SP-HA



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/D37SUB/M/ET200SP-HA
Catalog number	1100964
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-B323131BB6
Generated	2026-08-04

Product Overview

VARIOFACE module for the SIMATIC ET200SP HA with push-in connections and male D-SUB connector, for mounting on NS 35 rails, 37-pos.

VARIOFACE module for SIMATIC ET200SP HA with push-in connections and D-SUB connector, for installation on DIN NS 35 rails, number of poles: 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1100964

Packing unit 1 pc

GTIN 4055626956541

Weight per Piece (excluding packing) 200.000 g

Custom tariff number 85369010

Country of origin US (United States)

Drawings

Dimensions

General

[Connection data 2](#)

[Standards and Regulations](#)

[Classifications](#)

[Note](#)

[Ambient conditions](#)

[Connection data](#)

[Supported controller](#)

[Environmental Product Compliance](#)

[Drawings](#)

[Circuit diagram](#)

[Back to top](#)[Note](#)

[Note Standard or halogen-free cables](#)

[Back to top](#)[Dimensions](#)

[Width 102.8 mm](#)

[Height 72.1 mm](#)

[Depth 46.6 mm](#)

[Back to top](#)[Ambient conditions](#)

[Ambient temperature \(operation\) -20 °C ... 70 °C](#)

[Ambient temperature \(storage/transport\) -20 °C ... 70 °C](#)

[Back to top](#)[General](#)

[Nominal voltage UN 25 V AC](#)

[60 V DC](#)

[Max. perm. current \(per branch\) 2 A](#)

[Number of positions 37](#)

[Status display No](#)

[Mounting position any](#)

[Back to top](#)[Connection data](#)

[Connection name Field level](#)

[Connection in acc. with standard IEC / EN](#)

[Connection method Push-in connection](#)

[Stripping length 8 mm](#)

[Number of positions 37](#)

[Conductor cross section solid 0.14 mm² ... 4 mm²](#)

[Conductor cross section flexible 0.14 mm² ... 2.5 mm²](#)

[Conductor cross section AWG 26 ... 14](#)

[Back to top](#)[Connection data 2](#)

[Connection name Controller level](#)

[Connection method D-SUB pin strip](#)

[Number of connections 1](#)

[Number of positions 37](#)

[Back to top](#)[Supported controller](#)

[Controller SIEMENS ET200SP HA](#)

[- suitable I/O card 6DL1131-6BH00-0PH1](#)

[6DL1131-6TH00-0PH1](#)

[6DL1131-6BL00-0PH1](#)

[6DL1132-6BH00-0PH1](#)

[6DL1132-6BL00-0PH1](#)

6DL1134-6TH00-0PH1
6DL1134-6JH00-0PH1
6DL1135-6TF00-0PH1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/D37SUB/M/ET200SP-HA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.