

INDUSTRIAL COMPONENT DATA

VIP-2/SC/D37SUB/M/ET200SP-HA 1100967 PHOENIX CONTACT VARIOFACE module for the SIMATIC ET200SP HA with screw ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D37SUB/M/ET200SP-HA



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/D37SUB/M/ET200SP-HA
Catalog number	1100967
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-757A950364
Generated	2026-08-06

Product Overview

VARIOFACE module for the SIMATIC ET200SP HA with screw connections and male D-SUB connector, for mounting on NS 35 rails, 37-pos.

VARIOFACE module for SIMATIC ET200SP HA with screw connections and D-SUB connector, for installation on DIN NS 35 rails, number of poles: 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 1100967

Packing unit 1 pc

GTIN 4055626953298

Weight per Piece (excluding packing) 200.000 g

Custom tariff number 85369010

Country of origin US (United States)

Drawings

Dimensions

General

Connection data 2

Standards and Regulations

Classifications

Note

Ambient conditions

Connection data

Supported controller

Environmental Product Compliance

Drawings

Circuit diagram

[Back to top](#)Note

Note Standard or halogen-free cables

[Back to top](#)Dimensions

Width 101 mm

Height 65.5 mm

Depth 45.1 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 70 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

[Back to top](#)General

Nominal voltage UN 25 V AC

60 V DC

Max. perm. current (per branch) 2 A

Number of positions 37

Status display No

Mounting position any

[Back to top](#)Connection data

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M 3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

[Back to top](#)Connection data 2

Connection name Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 37

[Back to top](#)Supported controller

Controller SIEMENS ET200SP HA

- suitable I/O card 6DL1131-6BH00-0PH1

6DL1131-6TH00-0PH1

6DL1131-6BL00-0PH1

6DL1132-6BH00-0PH1

6DL1132-6BL00-0PH1

6DL1134-6TH00-0PH1

6DL1134-6JH00-0PH1

6DL1135-6TF00-0PH1

[Back to top...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/D37SUB/M/ET200SP-HA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.