

INDUSTRIAL COMPONENT DATA

VIP-2/SC/FLK16/ISP 4AI 2DMU 2903869 PHOENIX CONTACT
Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/FLK16/ISP 4AI 2DMU



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/FLK16/ISP 4AI 2DMU
Catalog number	2903869
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-E748726FBA
Generated	2026-08-02

Product Overview

Passive module

VARIOFACE Professional (VIP) module for Siemens ET200 ISP control systems. HART interface with analog input, 4 channels. 125 V AC/DC, rating 1 A, bipolar.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2903869

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356827546

Weight per Piece (excluding packing) 333.330 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 45 mm

Height 65.5 mm

Depth 56 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 60 V AC/DC

Max. perm. current (per branch) 1 A

Number of positions 16

Status display No

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M 3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 16

Pitch 2.54 mm

Supported controller

Controller Siemens ET200 ISP

- suitable I/O card 6ES7134-7TD00-0AB0

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss 7.027141152eCl@ss

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/FLK16/ISP 4AI 2DMU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.