

INDUSTRIAL COMPONENT DATA

VIP-3/PT/FLK50/AN/2P/S7-1500 2908499 PHOENIX CONTACT

Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/FLK50/AN/2P/S7-1500

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/FLK50/AN/2P/S7-1500
Catalog number	2908499
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-CD17A2AD62
Generated	2026-08-05

Product Overview

Passive module

VARIOFACE COMPACT LINE interconnect module for Siemens S7-1500 systems with specific marking S7-1500, with push-in connection, connections for external power distribution, module width: 128.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2908499

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 512 (C-5-2017)

GTIN 4055626363516

Weight per Piece (excluding packing) 314.300 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 128.2 mm

Height 75.8 mm

Depth 63 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 60 V AC/DC

Max. perm. current (per branch) 1 A

Max. permissible current (separate power supply) 7 A

Number of positions 50

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 26 ... 14

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 50

Pitch 2.54 mm

Supported controller

Controller SIEMENS S7-1500

- suitable I/O card 6ES7 531-7KF00-0AB0

6ES7 531-7NF00-0AB0

6ES7 531-7NF10-0AB0

6ES7 531-7PF00-0AB0

6ES7 532-5HF00-0AB0

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/FLK50/AN/2P/S7-1500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.