

INDUSTRIAL COMPONENT DATA

VIP-PA-FLK50/ 3,0M/S7 2322485 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-PA-FLK50/ 3,0M/S7



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-PA-FLK50/ 3,0M/S7
Catalog number	2322485
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-2E43BD084F
Generated	2026-08-01

Product Overview

Front adapters

VIP VARIOFACE front adapter, with connected system cables for SMATIC S7-300, connectable 1 x 32 channels, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2322485

Packing unit 1 pc

Catalog page Page 500 (C-5-2017)

GTIN 4046356451925

Weight per Piece (excluding packing) 720.800 g

Custom tariff number 85444290

Country of origin DE (Germany)

Note

Type of note Notes on operation

Note Analog I/O cards

To avoid short-circuits, all wire bridges must be disconnected!

No voltage supply may be supplied to the front adapter!

Type of note Notes on operation

Note Digital I/O cards

Thanks to the existing wire bridge upon delivery, the input and output bytes are non-isolated.

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. permissible operating voltage < 50 V AC

60 V DC

Max. permissible current 1 A (per path)

8 A (Separate power supply)

Mounting position any

Degree of protection IP20

Connection data 1

Connection name Control side

Connection method Plug connection

Note Can be plugged onto 40-pos. I/O modules

Connection data 2

Connection name Field level

Connection method IDC/FLK socket strip

Number of connections 1

Number of positions 50

Pitch 2.54 mm

Connection data 3

Connection name Supply

Connection method Push-in connection

Stripping length 10 mm

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 14

Cable

Conductor construction: Number of litz wires: 7

Single wire, material Cu tin-plated

Single wire, cross section 0.14 mm²

External diam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-PA-FLK50/ 3,0M/S7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.