

**INDUSTRIAL COMPONENT DATA**

# VIP-PA-FLK50/BRIDGE-SET/S7-AO 1017706 PHOENIX CONTACT Jumper

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-PA-FLK50/BRIDGE-SET/S7-AO



|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                           |
| MPN / Reference | VIP-PA-FLK50/BRIDGE-SET/S7-AO                             |
| Catalog number  | 1017706                                                   |
| Category        | Accessories/spare parts for low-voltage switch technology |
| Minimum order   | 1 Pcs                                                     |
| Document ID     | EO-7F1D4C8CAE                                             |
| Generated       | 2026-08-06                                                |

## Product Overview

Jumper

Set of jumpers for 40-pole VIP-S7 adapter for positive and negative classification.

Bridging set for 40-pos. VIP S7 adapter for plus and minus marshalling.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                             |
|--------------|---------------------------------------------|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |
|--------------|---------------------------------------------|

## Additional Product Information

Technical dataNotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Product propertiesProduct type Bridge

Insulation characteristics: Air clearances and creepage distances

Insulation Functional insulation

Overvoltage category II

Pollution degree 2

Electrical propertiesNominal voltage UN 25 V AC

60 V DC

Nominal current IN 3 A

Air clearances and creepage distances

Rated insulation voltage < 50 V

Rated surge voltage 0.5 kV (1.2/50 us)

Environmental and real-life conditions Ambient conditions

Degree of protection IP00

Ambient temperature (operation) -20 °C ... 50 °C

Altitude ≤ 2000 m

Standards and regulations Air clearances and creepage distances

Standards/regulations DIN EN 50178: 1998-04

Mounting Mounting type Load-free, pluggable (with needle-nose pliers)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-PA-FLK50/BRIDGE-SET/S7-AO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.