

## INDUSTRIAL COMPONENT DATA

## VIP/S/MC/BASE 9-16/L/EX 2906630 PHOENIX CONTACT Base module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP/S/MC/BASE 9-16/L/EX



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | VIP/S/MC/BASE 9-16/L/EX |
| Catalog number  | 2906630                 |
| Category        | Interface module        |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-1BC17DA632           |
| Generated       | 2026-08-03              |

## Product Overview

## Base module

Marshalling 8-channel VIP I/O base element for universal use. All connections as screw connection technology. With the COMBICON connector, compatible with the Honeywell C300 RUSIO series. Labeling for channels 9-16.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

## Key Commercial Data

Orderkey 2906630

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 553 (C-5-2017)

GTIN 4055626184623

Weight per Piece (excluding packing) 414.600 g

Custom tariff number 85366990

Country of origin US (United States)

## Dimensions

Width 118.1 mm

Height 102.7 mm

Depth 72.2 mm

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 75 °C

**General**Max. operating voltage  $U_{max}$  30 V DC (P2 and field terminals)

Max. operating voltage 30 V DC (P2 and field terminals)

230 V AC (P2 and field terminals)

30 V DC (P1 terminals)

30 V (X30 and X31 connectors)

Max. perm. current (per branch) 3 A (field signal)

1 A (control contacts)

Max. permissible current 15 A ()

Max. permissible total current 15 A (per module)

Status display No

Mounting position As desired on 35 mm DIN rail in acc. with EN 60715

Degree of protection IP20

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Torque 0.5 Nm ... 0.6 Nm

Connection data for connection 2

Connection name Controller level

Connection method Pluggable screw connection

Number of connections 2

Number of positions 9

Supported controller

Controller universal

Safety data

Input voltage  $U_i$  30 V (per ch...**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / VIP/S/MC/BASE 9-16/L/EX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.