

INDUSTRIAL COMPONENT DATA

VS-08-SD 1689200 PHOENIX CONTACT Protective covers

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-08-SD



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-08-SD
Catalog number	1689200
Category	Cap for industrial connectors
Minimum order	5 Pcs
Document ID	EO-86F1A6CD38
Generated	2026-08-01

Product Overview

Protective covers

Protective cap, IP67, high workmanship

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1689200

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 34 (PC-2005)

GTIN 4017918878016

Weight per Piece (excluding packing) 4.240 g

Custom tariff number 39235090

Country of origin DE (Germany)

Mechanical characteristics

Connection profile RJ45

Locking type without

Color gray

Degree of protection IP67

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Material data

Flammability rating according to UL 94 V0

Housing material PA

Material Plastic

Sealing material FPM

Seal material FPM

Height 33 mm

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141210eCl@ss 4.127141210eCl@ss 5.027149110eCl@ss 5.127149100eCl@ss 6.027261200eCl@ss
7.027440208eCl@ss 8.027440208eCl@ss 9.027440208

ETIM 2.0EC000241ETIM 3.0EC002040ETIM 4.0EC002040ETIM 5.0EC002314ETIM 6.0EC002314

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.239121421

ETIM for 1689200 Connectors (EC002314)

Feature Name

Feature Value

Type of locking (EF000208)

None

With sealing (EF005610)

No

With captivity element (EF012222)

No

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

80 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-08-SD with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.