

INDUSTRIAL COMPONENT DATA

VS-IP20-IP20-93C/1,0 1404372 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-IP20-IP20-93C/1,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-IP20-IP20-93C/1,0
Catalog number	1404372
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-41BCDE0CA1
Generated	2026-08-05

Product Overview

Network cable

Ready-made PROFINET cable, CAT5e, shielded, star quads, AWG 22 suitable for power supply chains (7 wires), RAL 6018 (yellow-green), RJ45/IP20 connector to RJ45/IP20 connector, length 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1404372

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356692410

Weight per Piece (excluding packing) 77.220 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -10 °C ... 60 °C (fixed routing)

-10 °C ... 60 °C (Flexibly installed)

General data

Number of positions 4
Overvoltage category I
Degree of pollution 1
Alternative short product description PROFINET cable
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Product labeling "sequential length in metres" PN-CABLE-934-C / PUR-4X22AWG/7 Trailing * 22AWG (SHIELDED) (UL)
E119100 CMX 75°C VERIFIED (UL) CAT 5E PATCH CABLE FRNC * (Cable printing cable supplier)
Cable type PROFINET drag chain CAT5
Cable type (abbreviation) 93C
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT®CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.5 mm
Wire colors White, yellow, blue, orange
Overall twist Star quad
Shielding Aluminum-coated foil, tinned copper braided shield
Optical shield covering 85 %
External sheath, color green RAL 6018
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 7.5 x D
Number of bending cy...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-IP20-IP20-93C/1,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.