

INDUSTRIAL COMPONENT DATA

VS-M12FSBP-OE-93E-LI/0,5 1413936 PHOENIX CONTACT

Conect. plug. to be apar. poster wall, CAT5 Ethernet (100 M..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12FSBP-OE-93E-LI/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M12FSBP-OE-93E-LI/0,5
Catalog number	1413936
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-A976E3FD3E
Generated	2026-08-03

Product Overview

Conect. plug. to be apar. poster wall, CAT5 Ethernet (100 MBit/s), CAT5 Ethernet (100 MBit/s), 4-pole, PUR, water blue RAL 5021, Connection female, straight, M12-SPEEDCON, D-coding, free cable end, Bus line, cable length: 0.5 m, 0.14 mm², CAT5 flexible Ethernet, 2 pairs, this item is expected to be lead-free from the first quarter of 2027 in accordance with RoHS II without exception 6c (Pb)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1413936

Packing unit 1

GTIN 4055626013411

Custom tariff number 85444290

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127060307eCl@ss 6.027061801eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 5.0EC002635ETIM 6.0EC002635

UNSPSC 13.239121413

ETIM for 1413936 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0

Number of control contacts (EF012217)

4

Type of housing (EF006980)

Straight

Rated current In (EF008250)

4 A

Ambient temperature (EF002386)

-25 °C

Rated voltage (EF000228)

48 V

Over voltage category (EF006785)

II

Pollution degree (EF006786)

3

Material of contact surface (EF004020)

Nickel

Housing material (EF001596)

Plastic

Material thread ring (EF012304)

Other

Type of locking (EF000208)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

With protective conductor (EF007468)

No

Degree of protection (IP), mounted (EF007466)

IP67

Min. number of insertion cycles (EF012212)

100

Screened (EF000881)

No

With status indication (EF001602)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12FSBP-OE-93E-LI/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.