

INDUSTRIAL COMPONENT DATA

VS-M12MS-IP20-94B-LI/15,0 1403376 PHOENIX CONTACT
Assembled Ethernet cable, shielded, 4-pair, AWG 26, strand..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12MS-IP20-94B-LI/15,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M12MS-IP20-94B-LI/15,0
Catalog number	1403376
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-AC3400DBF8
Generated	2026-08-05

Product Overview

Assembled Ethernet cable, shielded, 4-pair, AWG 26, stranded (7-wire), RAL 5021 (aqua blue), M12 plug to RJ45 plug/IP20, line, length 15 m

Confec., shielded, 4 pairs, flexible AWG 26 (7 wires), RAL 5021 (aqua blue), connector. M12 male in conec. RJ45/IP20 male, Line, long. 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1403376

Packing unit 1 pc

Minimum order quantity 25 pc

GTIN 4046356649629

Weight per Piece (excluding packing) 740.000 g

Custom tariff number 85444210

Country of origin PL (Poland)

Drawings

Ambient conditions

Standards and Regulations

Environmental Product Compliance

Dimensions

General data

Cable

Classifications

Drawings

Dimensional drawing

Plug, M12 x 1, straight, shielded

Dimensional drawing

Circuit diagram

Cable cross section

Ethernet, flexible, CAT5 [94B]

[Back to top](#)Dimensions

Length of cable 15 m

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (cable, fixed installation)

-5 °C ... 60 °C (cable, flexible installation)

[Back to top](#)General data

Rated voltage 30 V AC

Number of positions 8

Degree of pollution 3

[Back to top](#)Standards and Regulations

Flammability rating according to UL 94 HB

[Back to top](#)Cable

Cable type Ethernet, flexible, CAT5

Cable type (abbreviation) 94B

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT5 (IEC 11801), 1 Gbps

Cable structure 4x2xAWG26/7; SF/UTP

Conductor cross section 4x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 0.96 mm

Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown

Twisted pairs 2 cores to the pair

Overall twist 4 pairs for core

Shielding Aluminum-coated foil, tinned copper braided shield

Optical shield covering 70 %

External sheath, color water blue RAL 5021

Outer....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12MS-IP20-94B-LI/15,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.