

INDUSTRIAL COMPONENT DATA

**VS-M12MSD-IP20-LI-93P/10,0 1445279 PHOENIX CONTACT
Assembled Ethernet cable, CAT5e, shielded, 2-pair, 26 AWG..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12MSD-IP20-LI-93P/10,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M12MSD-IP20-LI-93P/10,0
Catalog number	1445279
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-251FE9FD76
Generated	2026-08-03

Product Overview

Assembled Ethernet cable, CAT5e, shielded, 2-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), M12 plug to RJ45 plug/IP20, line, length: 10 m

Ready-made Ethernet cable, CAT5e, shielded, 2-pair, flexible AWG 26 (7-wire), RAL 5021 (water blue), male connector M12 to male connector RJ45/IP20, line, length 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1445279

Packing unit 1

GTIN 4046356582643

Custom tariff number 85444290

Drawings

Ambient conditions

Standards and Regulations

Classifications

Dimensions

General data

Environmental Product Compliance

Drawings

[Dimensional drawing](#)

[Plug, M12 x 1, straight, shielded](#)

[Dimensional drawing](#)

[RJ45 connector, IP20](#)

[Back to top](#)[Dimensions](#)

[Length of cable 10 m](#)

[Back to top](#)[Ambient conditions](#)

[Ambient temperature \(operation\) -25 °C ... 60 °C \(cable, fixed installation\)](#)

[-5 °C ... 50 °C \(cable, flexible installation\)](#)

[Back to top](#)[General data](#)

[Rated voltage 48 V AC](#)

[60 V DC](#)

[Number of positions 4](#)

[Signal type/category Ethernet CAT5 \(IEC 11801:2002\)](#)

[Degree of pollution 3](#)

[Alternative short product description Ethernet cable](#)

[Back to top](#)[Standards and Regulations](#)

[Flammability rating according to UL 94 V2](#)

[Back to top](#)[Environmental Product Compliance](#)

[REACH SVHC](#)

[Lead 7439-92-1](#)

[China RoHS Environmentally Friendly Use Period = 50](#)

[For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 4.0 27060300](#)

[eCl@ss 4.1 27060300](#)

[eCl@ss 5.0 27060300](#)

[eCl@ss 5.1 27060300](#)

[eCl@ss 6.0 27279200](#)

[eCl@ss 7.0 27279218](#)

[eCl@ss 8.0 27279218](#)

[eCl@ss 9.0 27060311](#)

[Back to top](#)[ETIM](#)

[ETIM 3.0 EC000830](#)

[ETIM 4.0 EC000830](#)

[ETIM 5.0 EC001855](#)

[ETIM 6.0 EC001855](#)

[ETIM 7.0 EC001855](#)

[Back to top](#)[UNSPSC](#)

[UNSPSC 6.01 31261501](#)

[UNSPSC 7.0901 31261501](#)

[UNSPSC 11 31261501](#)

[UNSPSC 12.01 31261501](#)

[UNSPSC 13.2 31251501](#)

[UNSPSC 19.0 31251501](#)

UNSPSC 20.0 31251501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12MSD-IP20-LI-93P/10,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.