

INDUSTRIAL COMPONENT DATA

VS-PNRJ45-PNRJ45-93K-10 1403874 PHOENIX CONTACT

Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PNRJ45-PNRJ45-93K-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PNRJ45-PNRJ45-93K-10
Catalog number	1403874
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-7EA0D0B343
Generated	2026-08-05

Product Overview

Patch cable

Sercos III Patch Cable, Shielded, Star Quad, Flexible AWG 22 (7 wires), RAL 3020 (Traffic Red), RJ45/IP20 Male Connector, Straight, to RJ45/IP20 Male, Straight, Length: 10 m

Sercos III patch cable, shielded, star-quad, 22 AWG stranded (7-wire), RAL 3020 (traffic red), RJ45 plug/IP20, straight, to RJ45 plug/IP20, straight, length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard

Sensor type Sercos

Number of positions 4

Shielded yes

Data management status

Article revision 04

Insulation characteristics

Overvoltage category I

Degree of pollution 1

SignalingStatus display no

Electrical properties Rated voltage (III/3) 72 V (DC)
Transmission medium Copper
Transmission characteristics (category) CAT5
Transmission speed 100 Mbps
Mechanical properties Mechanical data
Insertion force per signal contact 30.00 N
Extraction force per signal contact 50 N
Material specifications Flammability rating according to UL 94 V0
Connector Connection 1
Type Plug straight RJ45
Shielded yes
Degree of protection IP20
Connection 2
Type Plug straight RJ45
Shielded yes
Insertion/withdrawal cycles ≥ 750
Degree of protection IP20
Cable/line Cable length 10.00 m
Sercos III [93K]
Dimensional drawing
Shielded yes
UL AWM Style 21694 (60 °C / 600 V)
Cable weight 68 kg/km
Cable type Sercos III
Cable type (abbreviation) 93K
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7, SF/TQ
External cable diameter 6.50 mm ± 0.2 mm
Outer sheath, material PVC
External sheath, color signal red RAL 3020
Thickness, outer sheath approx. 0.90 mm
Material, inner sheath PVC
Conductor material Tin-plated Cu litz wires
Conductor structure signal line 7x 0.25 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm²
Material wire insulation PE
Wire diameter incl. insulation approx. 1.55 mm
Singl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PNRJ45-PNRJ45-93K-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.