

INDUSTRIAL COMPONENT DATA

VS-PNRJ45-PNRJ45-93K-4 1404491 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PNRJ45-PNRJ45-93K-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PNRJ45-PNRJ45-93K-4
Catalog number	1404491
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-477A82BC94
Generated	2026-08-04

Product Overview

Bus system cable

Sercos III patch cable, shielded, star quad, flexible AWG 22 (7 wires), RAL 3020 (traffic red), RJ45/IP20 connector, straight, in RJ45/IP20 connector, straight, length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1404491

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356698313

Weight per Piece (excluding packing) 297.400 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP20

General data

Number of positions 4

Degree of pollution 1

Rated voltage (III/3) 72 V (DC)
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type Sercos III
Cable type (abbreviation) 93K
UL AWM style 21694 (60°C / 600 V)
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation approx. 1.55 mm
Wire colors White, yellow, blue, orange
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Shielding Tinned copper braided shield
External sheath, color signal red RAL 3020
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed installation 3 x D
Minimum bending radius, flexible installation 7 x D
Cable weight 68 kg/km
Outer sheath, material PVC
Material, inner sheath PVC
Material conductor insulation PE
Conductor material Tin-plated Cu litz wires
Insulation resistance $\geq 0.5 \text{ G}\cdot\text{km}$
Conductor resistance $\leq 120 \text{ }\Omega/\text{km}$
Wave impedance $100 \text{ }\Omega \pm 15 \text{ }\Omega$ (at 100 MHz)
Signal runtime 5.3 ns/m
Coupling resistance $\leq 20.00 \text{ m}\Omega/\text{m}$ (at 10 Hz)
Nominal voltage, cable 600 V
Test voltage C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PNRJ45-PNRJ45-93K-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.