

INDUSTRIAL COMPONENT DATA

VS-PPC-F1-RJ45-MNNA-1C-FJJ 1405332 PHOENIX CONTACT

Panel mounting frames

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F1-RJ45-MNNA-1C-FJJ



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-F1-RJ45-MNNA-1C-FJJ
Catalog number	1405332
Category	Fixing element for industrial connectors
Minimum order	1 Pcs
Document ID	EO-671DF6CB1D
Generated	2026-08-06

Product Overview

Panel mounting frames

RJ45 recessed frame, IP67, for push-pull locking, metal, with Freenet system, for circular mounting opening, with RJ45 female/female insert, with gasket, without fixing screws

RJ45 Mounting Frame, IP67, for Push-Pull Locking, Metal, with Freenet System, for Round Mounting Cutout, with RJ45 Socket Socket Socket/Socket, with Gasket, without Mounting Screws

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1405332

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356420433

Weight per Piece (excluding packing) 70.440 g

Custom tariff number 85444995

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 8

Number of slots 2

Locking type Push Pull

Insertion/withdrawal cycles ≥ 100

Color silver

Degree of protection IP65/IP67

Type RJ45, IP65/67, version 14

Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling) and chapter 13 Application specific Cabling and Interconnection Technology (AIDA)

Ambient conditions

Ambient temperature (operation) $-40\text{ }^{\circ}\text{C} \dots 70\text{ }^{\circ}\text{C}$

Material data

Housing material Zinc die-cast

Housing surface material Nickel-plated

Material Metal

Sealing material NBR

Height 42 mm

Electrical characteristics

Number of positions 8

Transmission characteristics (category) CAT5 (IEC 11801:2002)

GRP transmission properties CAT5 (IEC 11801:2002)

Degree of pollution 2

Rated voltage (III/3) 72 V (DC)

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027261200eCl@ss 7.027440210eCl@ss 8.027440210eCl@ss 9.0274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F1-RJ45-MNNA-1C-FJJ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.