

INDUSTRIAL COMPONENT DATA

WST 4 3030954 PHOENIX CONTACT Warning cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: WST 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	WST 4
Catalog number	3030954
Category	Warning/signing plate
Minimum order	50 Pcs
Document ID	EO-65357D5B68
Generated	2026-07-31

Product Overview

Warning cover

Warning cover, Strips, yellow, labeled, mounting type: plugged in, for terminal width: 6.2 mm, usable area: 4.5 x 5.55 mm, Number of individual indexes: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 3030954

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 163 (C-3-2017)

GTIN 4017918193119

Weight per Piece (excluding packing) 0.400 g

Custom tariff number 49119900

Country of origin PL (Poland)

Dimensions

Length (b) 4.5 mm

Width (a) 6.2 mm

Height (c) 1 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

General

Color yellow

Type high

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 5

Number of individual labels per row 5

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type Plug in

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V2

Classifications

eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.0271411...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WST 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.