

INDUSTRIAL COMPONENT DATA

PML-W100 (100X100)R CUS 0830495 PHOENIX CONTACT

Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W100 (100X100)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W100 (100X100)R CUS
Catalog number	0830495
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-C87F36345F
Generated	2026-08-05

Product Overview

Warning label

Warning plate, available: by lines, yellow/black, labelled according to customer specifications: White, mounting type: glued, diameter: 0 mm, usable area: 100 x 100 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830495

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 321 (C-5-2013)

GTIN 4046356718073

Weight per Piece (excluding packing) 1.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 100 mm

Width (a) 100 mm

Height (c) 86.8 mm

Diameter 0.00 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 90 °C

Ambient temperature (assembly) > 8 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow/black

Type Triangle

Components Silicone-free

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing Blank

Number of individual labels 250

Number of individual labels per row 1

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Marking mounting type adhesive

Standards and Regulatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W100 (100X100)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.