

INDUSTRIAL COMPONENT DATA

US-PML-W100 (25X25) 1014125 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-PML-W100 (25X25)



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-PML-W100 (25X25)
Catalog number	1014125
Category	Warning/signing plate
Minimum order	10 Pcs
Document ID	EO-1FE345836A
Generated	2026-08-05

Product Overview

Warning label

Warning plate, Card, yellow/black, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, diameter: 0 mm, useful surface: 25 x 25 mm, Number of individual indexes: 24

Warning label, Card, yellow/black, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, diameter: 0 mm, Number of individual labels: 24, text field height: 25 mm, text field width: 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Warning label unprinted

Area of application Warning labels

Warning identification according to ISO 7010

Type Triangle

Data management status

Article revision 02

Marking

Number of individual labels 24

Identification technology Thermal transfer for sheets and cards

DimensionsWidth 25 mm
Text field width 25.00 mm
Height 21.65 mm
Text field height 25.00 mm
Length 25 mm
Diameter 0.00 mm
Material specificationsColor yellow/black
Material PVC
Components Silicone-free
Environmental and real-life conditionsScratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements ≥ 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification DIN EN ISO 4892-2:2021-11 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
Ethanol (99 %)
[CAS No. 64-17-5] Test passed
Diesel
[CAS No. 68476-34-6] Test passed
IRM 901 Test passed
IRM 902 Test passed
Testing in a condensation chang...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-PML-W100 (25X25) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.