

INDUSTRIAL COMPONENT DATA

PML-W100 (50X50)R 0830430 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W100 (50X50)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W100 (50X50)R
Catalog number	0830430
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-BD61A16B07
Generated	2026-08-03

Product Overview

Warning label

Warning plate, Roll, yellow/black, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: glued, diameter: 0 mm, useful surface: 50 x 50 mm, Number of individual indexes: 500

Warning plate, Roll, yellow/black, unlabeled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: glued, diameter: 0 mm, Number of individual indexes: 500, text field height: 50 mm, text field width: 50 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830430

Packing unit 1 pc

Catalog page Page 369 (C-3-2017)

GTIN 4046356717540

Weight per Piece (excluding packing) 349.600 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 50 mm
Width (a) 50 mm
Height (c) 43.3 mm
Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 8 °C
Recommended storage conditions 4°C - 40°C
Storage in the original packaging is recommended.

General
Color yellow/black
Type Triangle
Components Silicone-free
Material PVC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 500
Number of individual labels per row 1
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146257 THERMOMARK S1.1
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W100 (50X50)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.