

INDUSTRIAL COMPONENT DATA

PML-W101 (50X50) 0830434 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W101 (50X50)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W101 (50X50)
Catalog number	0830434
Category	Warning/signing plate
Minimum order	5 Pcs
Document ID	EO-4CC220F65A
Generated	2026-08-01

Product Overview

Warning label

Warning plate, Elbow, yellow/black, labeled: Lightning with arrow, mounting class: glued, diameter: 0 mm, usable surface: 50 x 50 mm, Number of individual indices: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > MS Material**

Additional Product Information

Key Commercial Data

Orderkey 0830434

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 370 (C-3-2017)

GTIN 4046356717588

Weight per Piece (excluding packing) 2.900 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 50 mm

Width (a) 50 mm

Height (c) 43.3 mm

Diameter 0.00 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 90 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow/black

Type Triangle

Components Silicone-free

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing Lightning flash

Number of individual labels 9

Number of individual labels per row 3

Adhesive Acrylic

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Environmental Product Compliance

REACH SVHC Reaction mass of DOTE and MOTE

Classifications

eCl@ss 10.0.140200202eCl@ss 4.024190219eCl@ss 4.1241902...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W101 (50X50) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.