

**INDUSTRIAL COMPONENT DATA**

# PML-W301 (52X26) 0830461 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W301 (52X26)



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | PML-W301 (52X26)      |
| Catalog number  | 0830461               |
| Category        | Warning/signing plate |
| Minimum order   | 5 Pcs                 |
| Document ID     | EO-867FA73222         |
| Generated       | 2026-07-29            |

## Product Overview

Warning label

Warning plate, Elbow, yellow/black, labeled: Lightning with arrow and warning in German, English, mounting class: glued, diameter: 0 mm, usable surface: 52 x 26 mm, Number of individual indices: 4

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > MS Material**

## Additional Product Information

Key Commercial Data

Orderkey 0830461

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 371 (C-3-2017)

GTIN 4046356717854

Weight per Piece (excluding packing) 5.570 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions

Length (b) 26 mm

Width (a) 52 mm

Height (c) 26 mm

Diameter 0.00 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 90 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow/black

Type Rectangle

Components Silicone-free

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing Lightning flash and warning in German, English

Number of individual labels 4

Number of individual labels per row 1

Adhesive Acrylic

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Environmental Product Compliance

REACH SVHC Reaction mass of DOTE and MOTE

Class...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W301 (52X26) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.