

**INDUSTRIAL COMPONENT DATA**

# PATG HF 3/30 1014061 PHOENIX CONTACT Conductor marker carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: PATG HF 3/30



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PATG HF 3/30                    |
| Catalog number  | 1014061                         |
| Category        | Mounting for labelling material |
| Minimum order   | 200 Pcs                         |
| Document ID     | EO-114BDB2E90                   |
| Generated       | 2026-08-04                      |

## Product Overview

Conductor marker carrier

Support for conductor signaling, transparent/black, unlabeled, mounting class: slip, cable diameter range: 4 ... 7 mm, usable surface: 30 x 4 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > MS Material**

## Additional Product Information

Key Commercial Data

Orderkey 1014061

Packing unit 200 pc

Minimum order quantity 200 pc

Note Made to Order (non-returnable)

Catalog page Page 258 (C-3-2017)

GTIN 4046356779487

Weight per Piece (excluding packing) 0.630 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Length (b) 30 mm

Width (a) 8.9 mm

Cable diameter 4 mm ... 7 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

General

Color transparent/black

Type Profile

Components free from silicone, halogen, and cadmium

Material TPU

RoHS compliant Yes

Marking mounting type slide on

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 33%

Class I 4

Class F 1

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

Standards and Regulations

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Classifications

eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.127400400eCl@ss 6.027149100eCl@ss

7.027149153eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC002248

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC

13.239131504

ETIM for 1014061 Domestic wiring accessories and controls (EC002248)

Feature Name

Feature Value

Material (EF002169)

Other

Width (EF000008)

8.9 mm

Self adhesive mounting (EF000097)

No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PATG HF 3/30 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.